Amendments to the Claims

1. (CURRENTLY AMENDED) A microcontroller (100) the programming of
which is carried out in at least one machine-dependent assembler language in which
the assembler commands, with the exception of conditional program jumps or
program branches, respectively, can be executed
in essence independently of data, characterized by at least one random
number generator (10)-assigned to the microcontroller (100) can be executed, by
means of which the program jumps or program branches can be executed
in dependence on the state of the random number generator (10) and/or
independently of the internal state of the programming of the microcontroller
(100) .
2. (CURRENTLY AMENDED) A microcontroller as claimed in claim 1,
characterized by at least one, in particular bit-addressable, random number register
(20)-assigned to the random number generator-(10).
3. (CURRENTLY AMENDED) A microcontroller as claimed in claim 1 or
2 <u>claim 1</u> , characterized by an embodiment as a smartcard controller.
4. (CURRENTLY AMENDED) An electrical or electronic device controlled by
means of at least one microcontroller (100) as claimed in at least one of claims 1 to
3 <u>claim 1</u> .
5. (CURRENTLY AMENDED) A method for processing the programming of a
microcontroller (100) executed in at least one machine-dependent assembler
language, the assembler commands, with the exception of conditional program jumps
or branches, being executed essentially independently of data, characterized in that
the program jumps or program branches are executed
- in dependence on the state of at least one random number generator
(10) and/or
independently of the internal state of the programming of the
microcontroller-(100).

- 6. (CURRENTLY AMENDED) A method as claimed in claim 5, characterized in that the random number generated by the random number generator (10) is read via software via registers and the random number read is then evaluated with a conditional program jump or branch.
- 7. (CURRENTLY AMENDED) A method as claimed in claim 5 or 6claim 5, characterized in that, if at least one, in particular bit-addressable, random number register (20)-is present, testing per bit of the random number register (20)-and a conditional jump or branch is carried out.
- 8. (CURRENTLY AMENDED) A method as claimed in at least one of claims 5 to 7claim 5, characterized by the implementation of at least one assembler command ("branch on random bit"), a defined bit of the random number register (20) being supplied, in particular directly, to the condition input for the conditional jump or branch.
- 9. (CURRENTLY AMENDED) A method as claimed in at least one of claims 5 to 8claim 5, characterized in that at least one Arithmetic Logic Unit (ALU) flag controlling the conditional jumps or branches is replaced, in particular via the software, by at least one bit of the random number register—(20), so that the conditional jumps or branches corresponding to the bit of the Arithmetic Logic Unit are controlled by the bit of the Random Number Register—(20).
- 10. (CURRENTLY AMENDED) A use of a microcontroller (100) as claimed in at least one of claims 1 to 3 and/or of a method as claimed in at least one of claims 5 to 9claim 5 for completely concealing the programming running on the microcontroller (100), so that at least one program running on the microcontroller (100) is unpredictable and non-reproducible for an external observer.